

BERCMAN®



MARINE-GRADE IP56

**WALLBOX DC CHARGER
BEW-60**

 Nasdaq Listed

www.bercman-energy.com

Features



- Weatherproof casing
- Customisable casing colors and custom sticker & wrapping options
- Quality charging cables
- LEDs for charging status indication
- Fit for outdoor and marine applications IP56 and IK10
- Emergency stop button
- Easy access for maintenance
- Wall-mounted or pedestal-mounted options

Technical Data

Bercman BEW-60	60
Maximum total DC power	60 kW
Operating Specification	
Outlet options	1 or 2 x CCS2
Display and status LEDs	10" touchscreen, RGB LED
Protection rating	IP56, IK10 (including display)
Ambient conditions	Operating temperature -40° C...+50° C < 95% relative humidity non-condensing
Electrical protection	Residual-current and surge protection, overvoltage protection, overtemperature protection
THDI	≤ 5 %
Power factor	> 0.99
Efficiency	≥96 %
Operating noise level	< 60 dB @ 5 m, full load
Grid Information	
Network type	TN-S
AC input voltage	400 V AC (±10%)
Maximum input current	94 A at 400 V AC
Frequency range	45...55 Hz
DC Outlet	
Max. current at charger's outlet	CCS2: 200 A peak (air-cooled cable), rated voltage 1000V
Output voltage range	150 – 1,000 V DC
General Specification	
Dimensions (HxWxD)	800 x 550 x 350 mm
Backend connectivity	OCPP 1.6J
Remote management	Remote access, over-the-air (OTA) software updates
Network connection	Ethernet, 4G LTE, 3G, 2G
Norms and Standards	
CE-certified	Yes
Safety and charging standard	IEC 61851-1, IEC 61851-21-2, IEC 61851-23
EV communication	DIN 70121, ISO 15118-2/-3
Connector	CCS Combo 2 cable acc. to IEC 62893-4-1:2020, based on IEC 62196-3
Charger cables	
Cable length	5/7 metres

Supporting Your Success



At Bercman, we are committed to delivering the highest quality products and services, ensuring world-class support throughout the full lifespan of your charging equipment. Our streamlined support processes guarantee a rapid response from our dedicated engineering team, providing expert assistance whenever you need it.



Beyond our standard solutions, we offer customisation options to meet specific requirements. Whether it's tailoring hardware configurations, adapting software functionalities, or developing unique charging solutions, we are ready to collaborate and create bespoke solutions that align with your needs.



Published by Bercman Technologies
Riia 26, Tartu, Estonia

For more information, please contact Bercman Energy
Phone: +372 5385 5877
E-mail: info@bercman-energy.com

© Bercman Technologies 2026

Made in **Europe** 

This document is subject to modifications and errors. The descriptions and performance characteristics provided herein are general in nature and may not accurately represent the described features or may change as product development progresses. Performance features become obligatory only if they are explicitly stipulated in the final contract.

All product names mentioned may be trademarks or subject to other rights of Bercman Technologies, its subsidiaries, or other entities, and unauthorized use by third parties could infringe upon the rights of the owners.